

# Genie Z 45 25 Specifications One One Source Rental

---

## [PDF] Genie Z 45 25 Specifications One One Source Rental

This is likewise one of the factors by obtaining the soft documents of this [Genie Z 45 25 Specifications One One Source Rental](#) by online. You might not require more period to spend to go to the books introduction as skillfully as search for them. In some cases, you likewise attain not discover the broadcast Genie Z 45 25 Specifications One One Source Rental that you are looking for. It will completely squander the time.

However below, like you visit this web page, it will be therefore categorically simple to acquire as skillfully as download guide Genie Z 45 25 Specifications One One Source Rental

It will not take many become old as we explain before. You can attain it even though bill something else at house and even in your workplace. appropriately easy! So, are you question? Just exercise just what we manage to pay for under as with ease as review **Genie Z 45 25 Specifications One One Source Rental** what you next to read!

### Genie Z 45 25 Specifications

#### **Self-Propelled Articulating Booms - Genie**

Specifications Z™-45/25 RT & Z Genie United States 6464 15th Ave N Redmond, WA 9052 Telephone 1 (425) 1100 Toll free in USA/Canada 1 (00)536100 a 1 (425) 3345 distributed by Features [www.genielift.com](http://www.genielift.com) Effective Date January, 2019 Product specifications and prices are subject to change without notice or obligation The photographs and/or

#### **Specifications**

[www.genieindustries.com.au](http://www.genieindustries.com.au) Z-45/25 J DC 090327 Ver1 Effective Date: April 2012 Product specifications and prices are subject to change without notice or obligation The photographs and/or drawings in this document are for illustrative purposes only

#### **GENIE Z45 25 RT SPECIFICATIONS - Durante Rentals**

Z™-45/25 RT • 51 ft 11 in (1600 m) working height • 25 ft (762 m) horizontal reach • 23 ft 6 in (716 m) up and over clearance • Up to 500 lb (227 kg) lift capacity Z™-45/25J RT ft 2 in (1607 m) working height GENIE Z45 25 RT SPECIFICATIONS Created Date:

#### **Self-Propelled Articulating Booms - Genie**

Z™-45/25J DC/Bi-Energy Specifications Models Z-45/25J DC & Bi \* The metric equivalent of working height adds 2 m to platform height US adds 6 ft to platform height \*\* In lift mode (platform raised), the machine is designed to operate on firm, level surfaces only \*\*\* Gradeability applies to driving on slopes

**Self-Propelled Articulating Booms**

Z™-45/25 & Z™-45/25J DC/Bi-Energy Specifications Models Z-45/25 DC & Bi Z-45/25J DC & Bi \* The metric equivalent of working height adds 2 m to platform height US adds 6 ft to platform height \*\* In lift mode (platform raised), the machine is designed to operate on firm, level surfaces only \*\*\* Gradeability applies to driving on slopes

**Z-45/25 RT & Z-45/25J RT Specifications**

rotation on Z-45/25 models | 160° hydraulic platform rotation on Z-45/25J models | Two- or four-wheel drive | AC wiring to platform | Drive enable system | Auxiliary power unit | Hour meter | Tilt alarm | Horn Z-45/25 RT & Z-45/25J RT Specifications SPECIFICATIONS Z-45/25 RT Z-45/25J RT US Metric US Metric Working height\* 51 ft 8 in 159 m 51

**SELF-PROPELLED ARTICULATING BOOMS ZTM-45/25 RT & ...**

Z TM-45/25 RT & Z TM-45/25J RT SELF-PROPELLED ARTICULATING BOOMS MODELS ZTM-45/25 RT ZTM-45/25J RT C D E A B F  
wwwgenieindustries.com Specifications \* The metric equivalent of working height adds 2 m to platform height

**Z-45/25 IC - Genie**

Serial Number Range from SN Z452507A-34011 to Z452513A-47000 Z-45/25 IC Z-45/25J IC from SN Z452507B-101 to Z452513B-3300 Part No 147545 Rev C3 November 2018

**Service Manual - Genie lift**

Z-45/25 • Z-45/25J Part No 107846 June 2012 ii Introduction Important Read, understand and obey the safety rules and operating instructions in the Genie Z-45/25 and Genie Z-45/25J Operator's Manual before attempting any maintenance or repair procedure

**Genie Z-45/25 RT & Z-45/25J RT Diesel Articulating Booms**

Genie Z-45/25 RT & Z-45/25J RT Diesel Articulating Booms n Self-levelling platform n Hydraulic platform rotation n Proportional joystick controls n Thumb rocker steering n Drive enable n AC power cord to platform n Horn n Hour meter n Tilt alarm n Descent & travel alarms n Flashing beacon n 355° non-continuous turntable rotation n Positive traction drive n Two speed wheel motors

**SELF-PROPELLED ARTICULATING BOOMS -45/25 & ZTM ...**

Z TM-45/25 & Z TM-45/25J IC Narrow SELF-PROPELLED ARTICULATING BOOMS Z45ICN 35K 0707J Part No 109363 wwwgenieindustries.com Effective Date: July, 2007 Product specifications and prices are subject to change without notice or obligation The photographs and/or drawings in this document are for illustrative purposes only

**SELF-PROPELLED ARTICULATING BOOMS excellenT PoSiTioninG**

Z TM-45/25 RT & Z TM-45/25J RT SELF-PROPELLED ARTICULATING BOOMS MODELS ZTM-45/25 RT ZTM-45/25J RT C D E A B F Specifications \* The metric equivalent of working height adds 2 m to platform height US adds 6 ft to platform height \*\* In lift mode (platform raised), the machine is designed to operate on firm, level surfaces only

**Specifications - Genie Lift**

Working height\* 647 m 20 ft 8 in 807 m 25 ft 11 in Platform height 447 m 14 ft 8 in 607 m 19 ft 11 in Platform dimensions (length Genie ® Runabout TM AERIAL WORK PLATFORMS Product specifications and prices are subject to change without notice or obligation The photographs and/or drawings in this document are for illustrative

**Genie Z34/22 Specifications - One Source**

Z TM-34/22 DC & Bi-Energy SELF-PROPELLED ARTICULATING BOOMS Z34DC/BI 0210L Part No 109359 wwwgenieindustriescom Effective Date: April, 2011 Product specifications and prices are subject to change without notice or obligation

**Specifications - Genie Lift**

wwwgenieindustriescomau Z-34/22N 090327 Ver1 Z TM-34/22N SELF-PROPELLED ARTICULATING BOOMS Effective Date: April 2012 Product specifications and prices are subject to change without notice or obligation The photographs and/or drawings in this document are for illustrative purposes only Refer to the appropriate Operators'

**Genie S-40-45 Specifications**

-45 SELF-PROPELLED TELESCOPIC BOOMS MODELS S TM-40 S TM-45 C D E A B F wwwgenieindustriescom Specifications \* The metric equivalent of working height adds 2 m to platform height US adds 6 ft to platform height \*\* Gradeability applies to driving on slopes See operator's manual for details regarding slope ratings

**Genie Z-45/25J DC/Bi-Energy Electric & Bi Energy ...**

Genie Z-45/25 & Z-45/25J DC/Bi-Energy Electric & Bi Energy Articulating Booms n Self-levelling platform n Hydraulic platform rotation n Proportional joystick controls n Thumb rocker steer n Drive enable n AC power to platform n Horn n Hour meter n Tilt alarm n Descent & travel alarms n Flashing beacon n 355° non-continuous turntable rotation n Zero tailswing n Certified load sensor

**Specifications - ABLE Equipment**

Z TM-45/25 RT & Z TM-45/25J RT SELF-PROPELLED ARTICULATING BOOMS Z45RT 35K 0307J Part No 109362 wwwgenieindustriescom For further information, please contact your local distributor or the Genie Industries sales office listed Product specifications are ...

**Maintenance Manual - Booms**

Maintenance Manual - Booms This manual includes detailed S Booms procedures for each maintenance inspection For Repair procedures, Fault Z Booms Codes, Electrical and Hydraulic